



Uniguard Tile Adhesive C2TE S2

Product Description

Uniguard Tile Adhesive C2TE S2 is a high-performance, highly deformable, one component, cementitious tile adhesive formulated for improved adhesion strength, flexibility, and resistance to movement. Suitable for bonding a wide range of tiles, including ceramics, porcelain, and natural stone, on both interior and exterior surfaces. The product is classified as S2 in accordance with EN12004.

Features and benefits

- Low viscosity, therefore easily workable.
- Highly thixotropic.
- Water and weather resistant: suitable for areas exposed to water and varying weather conditions.
- Flexible and highly deformable to accommodate structural movement and thermal changes.
- Perfect adherence to all materials normally used in building.
- Extended open time which allows for more working time during installation.
- Can be used internally and externally.

Typical use

- Suitable for use with large variety of tiles including ceramic, porcelain and natural stone tiles.
- Excellent workability and non-slip properties, ideal for fixing large format tiles.
- Suitable for wet and dry areas, including bathrooms, kitchens, and swimming pools.

Substrate

Plaster, concrete, block work, cement board, etc....

Product Data

Packaging size	25 Kg
Form	Powder
Colors	White
Powder Density	0.90 - 1.00 g/cm ³
Mixed Density	1.10 - 1.15 g/cm ³
Slip Resistance	< 0.5mm
Pull off Strength	≥ 1 MPa
Open Time	≥ 30 minutes
Deformability	≥ 5 mm



Caution

- Clean mixing container before use. Do not use dirty tools.
- Do not exceed dilution ratios.
- Keep out of the reach of children.

Health and safety

Possible Hazards: it causes irritation in case of skin contact & eye contact, flush immediately with plenty of water for at least 10 minutes and seek medical advice in case it happened.