

Deep Clean Attack

Product Description

Deep Clean Attack is a powerful, acidic cleaner designed for the effective removal of stains, residues, and contaminants from concrete and stone surfaces. Its formulation includes muriatic acid and caustic soda, providing superior cleaning properties while being emulsifiable in water for ease of use.

Features and benefits

- Easy to use.
- Fast acting.
- Works quickly to penetrate and dissolve grease.
- Removes tough grease and grime, ensuring surfaces are thoroughly cleaned.

Typical use

- Cleaning and preparation of concrete surfaces before coating or sealing.
- Removal of efflorescence, rust, and lime deposits from stone or masonry.
- Effective for industrial and construction site maintenance.

Substrate

Works well on a wide variety of substrates such as metal, concrete, plastic, ceramic and tile, glass, rubber, wood, kitchen appliances and any absorbent surface.

Product Data

Packaging size 5 L

Form Liquid

Appearance Yellow

Density 1.00 g/cm³

Application data

The product can be applied directly from the bottle using the below:

Brush Recommended

Spray Recommended

Cleaning of painting tools

Immediate cleaning with water is necessary.

Film Thickness per coat

Dry film thickness NA

Theoretical spreading rate NA

Spreading rates depend on the conditions of the substrate.

Technical Data Sheet



Thinner (solvent to mix with)

Ready for application

Dilution (Mix Ratio)

Ready for application, water can be used.

Conditions during application

Do not apply if the temperature is below 5°C and not more than 60°C. Avoid working under direct sunlight.

Drying and curing time

25 °C

Surface (touch) dry

NA

Dry to over coat, minimum

NA

Full Cure

NA

Directions for use

Surface Preparation

- Ensure the surface is free of loose dirt and dust before application.
- The product can be diluted with water depending on the severity of the contamination. Typical dilution ranges from 1:1 to 1:5.
- Apply the diluted solution to the surface using a brush or spray. Allow it to react for several
 minutes, depending on the level of contamination. Avoid letting the product dry on the
 surface
- Rinse the treated area thoroughly with clean water to remove all residues.

Recommended Paint System

Number of coats:

Apply as much as necessary.

Storage

- Store in cool, dry place in a well-sealed container for 12 months.
- Keep away from heat, ignition sources and from children.

Caution

- Do not use dirty tools.
- Keep out of the reach of children.
- Avoid contact with skin and eyes. Use appropriate protective equipment, including gloves and goggles.

Health and safety



Technical Data Sheet

Possible Hazards: it causes irritation in case of skin contact & eye contact, flush immediately with plenty of water for at least 10 minutes and seek medical advice in case it happened. For more information, refer to product material safety data sheet.

Date of issue:19.10.2024 Rev01 Page: 3/3