

## **Technical Data Sheet**

# **Bituguard Plus**

## **Product Description**

Bituguard Plus is a highly rubberized bitumen emulsion. It dries to form a black, very flexible coating.

### **Features and benefits**

- Single component, easy to apply.
- Solvent free, nonflammable.
- Friendly to environment.
- Asbestos free.

## Typical use

- **General waterproofing:** for use on concrete (exposed or below ground), cement, roofing felt, terraces, kitchens, bathrooms floors, plantation beds, and under floor tiles, as a water and moisture barrier. It is most effective when cracks are expected in the surface.
- Curing compound on freshly cast concrete surfaces to reduce the loss of water during the early hardening period.
- Vapor Barrier: it is used as a vapor barrier when applied on concrete surfaces below insulation.
- **Dampproofing:** for protection of underground foundations.

## **Product Data**

Packaging size 20 Liter
Form Liquid

**Colors** Dark brown **Residues by evaporation** 55 ± 5%

**Density**  $0.98 - 1.04 \text{ g/cm}^3$ 

Elasticity >100%

## **Application data**

The product can be applied by

Roller Recommended
Brush Recommended

### Cleaning of painting tools

Immediate cleaning with water is necessary. Use white spirit in the material has dried.

### Film Thickness per coat

Consumption 0.75 kg/m<sup>2</sup>

Date of issue:1710.2024 Rev03 Page: 1/2



## **Technical Data Sheet**

## Thinner (solvent to mix with)

Water

## **Dilution (Mix Ratio)**

Not needed

## **Conditions during application**

Do not apply if the temperature is below 5°C and not more than 45°C. Avoid working under direct sunlight.

Drying and curing time 25 °C

Surface (touch) dry 2 h

Dry to over coat, minimum 6 h

Full Cure 24 h

#### **Directions for use**

### **Surface preparation**

- Ensure that surface is thoroughly cleaned and free from grease, oil, dirt, salt and other containment.
- Clean the surface with water.

## **Recommended Paint System**

#### Number of coats:

Apply 2 – 3 coats of Bituguard Plus.

#### **Storage**

- Store in cool, dry place in a well-sealed container away from moist air for 6 months.
- Keep away from heat, ignition sources and from children.
- Never expose to freezing.

#### Caution

- Clean mixing container before use. Do not use dirty tools.
- Do not exceed dilution ratios.
- Keep out of the reach of children

### **Health and safety**

Possible Hazards: It causes irritation in case of skin contact & eye contact, flush immediately with plenty of water for at least 10 minutes and seek medical advice in case it happened. For more information, refer to technical data sheet.

Date of issue:1710.2024 Rev03 Page: 2/2